

## G15-SUB

## G15-SUB

Compact high output subwoofer



- Coda Audio 15" ultra low distortion neodymium woofer
  - Extended frequency response down to 38 Hz
  - System integration with the G500-Series 2-way full range systems
  - Maximum SPL 138 dB (peak)
  - Low power compression
- System components: C10, DNC260, G308, G512-96, G515-96

The G15-SUB is a 15" compact subwoofer that provides powerful low frequency response. Low port compression and optimized enclosure design give a tight, accurate bass response that is ideally suited as a sub-extension for the G500-Series systems.

#### State-of-the-art drivers

The G15-SUB is equipped with an extremely long excursion 15" neodymium ultra low distortion woofer. The neodymium motor delivers extreme high magnetic flux for increased efficiency. The 4" voice coil is 38 mm high, ensuring ultra linear excursion of 26 mm / pp at consistent magnetic force. State-of-the-art carbon-fiber cone ensures maximum stiffness and low moving mass.

Three aluminum shorting rings reduce intermodulation distortion, minimize induction variation while reducing thermal compression. This design dramatically reduces the distortion of a typical subwoofer at longer excursion levels, and improves the overall sound quality and performance characteristics of the cabinet.

#### Applications

The G15-SUB is perfectly suited as a sub-extension for the G500-Series systems and can be used in Houses of Worship, Theatres, clubs and mobile applications.

#### TECHNICAL SPECIFICATIONS G15-SUB

Type:	15" subwoofer
Application:	Compact high output subwoofer
Frequency response (-6 dB):	38 Hz - 180 Hz
Power handling (AES/peak):	1250 W / 5000 W
Sensitivity 1 W / 1 m:*	101 dB
Maximum output peak:**	138 dB
Components:	15" neodymium ultra low distortion woofer, 4" (101.6 mm) voice coil, 1250 W (AES)
Nominal impedance:	8 Ohm, +1 / -1
Input connectors:	2x Neutrik™ NL4MP
Suspension:	Optional
Enclosure material:	Baltic birch
Finish:	Textured black paint
Dimensions:	520 x 431 x 630 mm
Net weight:	34 kg

\* Half-space loading

\*\*Measured with pink noise 6 dB crest factor